

95543

Hero CCT Step Dim

FEATURES

- 5 years (2 years + 3 years) extended warranty
- Gloss white & opal PC finish
- Constructed from polycarbonate
- Complete with built in step dim microwave sensor
- IP65
- IK10
- Fast fit hinged gear tray
- Interchangeable bezels

SPEC DATA

Product Wattage:	9/14/18W
Product Lumen:	900/1400/1800Lm
Lumen/W:	100
Kelvin:	3000/4000/6000K
Energy Rating:	A+
Dimmable:	No
Beam Angle:	120°
Power Factor:	>0.9
CRI:	>80
Lifetime (Hours):	35000
LED Brand:	Epistar
SDCM:	<6
Driver Type:	Constant Current 180mA
Product Voltage:	220-240V
Hertz:	50/60
Surge Protection (KV):	1.5
Operating Temp.:	-20 to 45 Degree
Product Weight (KG):	0.82
Terminal Block:	3-way fast fix
Class:	2

Step Dim Microwave Movement Sensor

DC Input Voltage:	12±1V DC
Rated Voltage:	12±0.6V DC
Stand-by Power:	<0.5W
Efficiency:	≥80%
Operating Frequency:	5.8 GHz ±75 MHz
Transmitting Power:	0.5mW Max.
Hold Time:	5s / 90s / 3min / 10min
Stand-by DIM Level:	20%
Stand-by Period:	0s / 30s / 10min / +∞
Detection Area:	100% / 75% / 50% / 25%
Daylight Sensor:	5Lux / 15Lux / 50Lux / Disable
Detecting Radius:	5m (mounting height 3m)
Mounting Height:	4m Max
Detecting Angle:	150°
Operating Temperature:	-25°C... +60°C
Storage Temperature:	Temperature: -40°C... +80°C; Humidity: 10% - 95% (non-condensing)

ACCESSORIES

95545, Hero chrome bezel	95550, Hero black grill bezel
95546, Hero white eyelid bezel	95551, Hero anthracite grey plain bezel
95547, Hero white grill bezel	95552, Hero anthracite grey eyelid bezel
95548, Hero black plain bezel	95553, Hero anthracite grey grill bezel
95549, Hero black eyelid bezel	

